

Typ	Einheit	40-6	40-7	45-6	45-7	50-6	50-7	60-6	60-7
Schnecken Ø		40 mm	40 mm	45 mm	45 mm	50 mm	50 mm	60 mm	60 mm
Verfahrenslänge LxD	Norm	25.D/30.D	25.D/30.D	25.D/30.D	25.D/30.D	25.D/30.D	25.D/30.D	25.D/30.D	25.D/30.D
Einzug		glatt	genutet	glatt	genutet	glatt	genutet	glatt	genutet
Lenze Antrieb DC	kW	11,4	11,4	22,7	22,7	27	27	46	46
Lenze Antrieb AC	kW	20,3	20,3	38,4	38,4	38,4	38,4	60,1	60,1
Getriebe	Nm	1.800	1.800	2.800	2.800	2.800	2.800	8.000	8.000
Heizbänder		Mica o. Keramik	Mica o. Keramik	Mica o. Keramik	Mica o. Keramik	Mica o. Keramik	Mica o. Keramik	Mica o. Keramik	Mica o. Keramik
Zylinder Heiz-Kühlzonen	25.D	4 pcs	4 pcs	4 pcs	4 pcs	4 pcs	4 pcs	4 pcs	4 pcs
Zylinder Heiz-Kühlzonen	30.D	5 pcs	5 pcs	5 pcs	5 pcs	5 pcs	5 pcs	5 pcs	5 pcs
Schneckendrehzahl	rpm	0-120	0-120	0-140	0-140	0-140	0-140	0-120	0-120